



Type 1F

Type 1

Type 2

Designation

| | | | |
|-----------------|-------|--------------|---------|
| 16 | T2.5 | 20 | F |
| Total width (M) | Pitch | Nb. of teeth | flasked |

Pitch T2.5 (2.5 mm) for Timing Belt - Width 6 mm

| Code | Pitch φ (outside φ) | Type | φ.d with pilot bore | φ.d * maxi. | L | outside φ Flask | M | N | φQ | Weight |
|-----------|---------------------|------|---------------------|-------------|----|-----------------|----|---|----|--------|
| 16T2.512F | 9.55 (9.00) | 1F | 4 | 6 | 9 | 13 | 16 | 7 | 12 | 0.003 |
| 16T2.514F | 11.14 (10.60) | 1F | 4 | 8 | 9 | 15 | 16 | 7 | 14 | 0.004 |
| 16T2.516F | 12.73 (12.20) | 1F | 4 | 8 | 10 | 15 | 16 | 6 | 14 | 0.005 |
| 16T2.518F | 14.32 (13.80) | 1 | 4 | 6 | 10 | 17.5 | 16 | 6 | 10 | 0.006 |
| 16T2.520F | 15.92 (15.40) | 1 | 4 | 6 | 10 | 19.5 | 16 | 6 | 12 | 0.008 |
| 16T2.522F | 17.51 (17.00) | 1 | 4 | 6 | 10 | 23 | 16 | 6 | 12 | 0.010 |
| 16T2.524F | 19.10 (18.55) | 1 | 4 | 6 | 10 | 23 | 16 | 6 | 12 | 0.012 |
| 16T2.525F | 19.89 (19.35) | 1 | 4 | 8 | 10 | 23 | 16 | 6 | 14 | 0.013 |
| 16T2.526F | 20.69 (20.15) | 1 | 4 | 8 | 10 | 25 | 16 | 6 | 14 | 0.015 |
| 16T2.528F | 22.28 (21.75) | 1 | 4 | 8 | 10 | 25 | 16 | 6 | 14 | 0.016 |
| 16T2.530F | 23.87 (23.35) | 1 | 6 | 10 | 10 | 28 | 16 | 6 | 16 | 0.018 |
| 16T2.532F | 25.48 (24.45) | 1 | 6 | 10 | 10 | 32 | 16 | 6 | 16 | 0.020 |
| 16T2.536F | 28.66 (28.10) | 1 | 6 | 12 | 10 | 37 | 16 | 6 | 20 | 0.026 |
| 16T2.540F | 31.83 (31.30) | 1 | 6 | 12 | 10 | 38 | 16 | 6 | 22 | 0.032 |
| 16T2.544F | 35.02 (34.50) | 1 | 6 | 14 | 10 | 43 | 16 | 6 | 24 | 0.040 |
| 16T2.548 | 38.20 (37.70) | 2 | 6 | 15 | 10 | | 16 | 6 | 26 | 0.048 |
| 16T2.560 | 47.75 (47.25) | 2 | 8 | 22 | 10 | | 16 | 6 | 34 | 0.073 |

* with keying : Norm NFE 22175

Cast iron FGL 250, Protection by phosphatation or black paint.